

# BLOCK PRIMER

## Acrylic, water-based primer – Stain blocker

### Description

Acrylic, white, water-based primer. It offers high adhesion and coverage, and blocks water-soluble stains on the substrate, so that they do not appear in the final color.

It is odorless, as well as environmentally and user friendly, thus recommended for use in interior, inhabited spaces.

### Fields of application

Suitable for indoor and outdoor use, on surfaces to be covered with emulsion or acrylic paints and substrates polluted with smoke, nicotine, exhaust fumes, water soluble markers, pencil stains, etc. It prevents the appearance of water-soluble stains in the final color.

### Technical data

Color:	white
Density:	1.40 kg/l
pH:	8.5
Adhesion:	> 2.5 N/mm <sup>2</sup>
Drying time:	1 h (touch dry)
Recoat time:	2.5 h

#### Cleaning of tools:

Remove as much of the product (remaining on the tools) as possible, before cleaning them. Clean tools with water and detergent, immediately after use.

### Directions for use

#### 1. Substrate preparation

The substrate must be dry and free of dust, grease, dirt, etc., while any imperfections must be restored.

#### 2. Application

BLOCK PRIMER is applied in one or two layers, depending on how stained the surface is. It may be thinned up to 10% with water, but in case of intense stains, it is recommended to use undiluted.

The surface may be recoated after 2.5 hours but it is recommended to apply the emulsion or acrylic, water-based paint after 24 hours, for higher effectiveness of the stain blocker. It is applied with a roller, brush or airless spray gun.

### Consumption

Approx. 11-16 m<sup>2</sup>/l per layer, depending on the absorbency of the substrate and the dilution ratio of the product.

### Packaging

0.75 l and 3 l containers.

### Shelf life – Storage

24 months from production date if stored in original unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

### Remarks

Temperature during application and drying of the primer should be between +10°C and +35°C.

### Volatile Organic Compounds (VOC)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory j, type WB is 30 g/l (2010) for the ready-to-use product.

The ready-to-use product BLOCK PRIMER contains a maximum of 30 g/l VOC.

#### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

#### MAIN OFFICES - FACTORY:

17<sup>th</sup> km Thessaloniki – Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: 22620 31 644

[www.isomat.eu](http://www.isomat.eu) e-mail: [info@isomat.eu](mailto:info@isomat.eu)