

# PRIMER CLASSIC

## Acrylic micronized water-based primer

### Description

PRIMER CLASSIC is an acrylic, micronized, water-based primer. It offers excellent bonding and high penetration. It is odorless, as well as environment and user friendly, therefore it is recommended for use in interior inhabited spaces. It has a slightly blue color in order to be easily visible in fully primed surfaces.

### Fields of application

It is suitable for use in new surfaces, such as plasters, concrete, bricks, etc., that are going to be covered with emulsion paints. Furthermore, it has the ability to harden and protect from moisture porous surfaces that are coated with lime, adhesives or old paint.

### Technical data

Form: emulsion

Color: blue

Density: 1.00 kg/l  
(EN ISO 2811-1)

pH: 8-9  
(EN ISO 4316)

Drying time: 1 h (touch day)  
(EN ISO 9117)

Recoat time: 4 h

Cleaning of tools:  
Remove as much paint as possible from the used tools before cleaning. Clean the tools thoroughly with water and detergent immediately after use.

### Directions for use

#### 1. Substrate

The surface to be primed must be dry and free of dust, grease, dirt etc. while any imperfections on plaster should be restored.

#### 2. Application

PRIMER CLASSIC is applied in one layer thinned up to 50% with clean water. For highly porous substrates use it undiluted.

It is applied by brush, roller or spraying.

### Consumption

About 10-15 m<sup>2</sup>/l per layer, depending on surface absorbency and thinning percentage.

### Packaging

PRIMER CLASSIC is available in plastic containers of 1, 5, 10 and 20 l.

### Shelf life – Storage

24 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sunlight and frost.

### Remarks

Temperature during application should be at among +10°C and +35°C.

### Volatile organic compounds (VOCs)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type WB is 30g/l (2010) for the ready-to-use product.

The ready-to-use product PRIMER CLASSIC contains max <30 g/l VOC.

**ISOMAT S.A.**  
BUILDING CHEMICALS AND MORTARS  
**MAIN OFFICES - FACTORY:**  
17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475  
**www.isomat.eu e-mail: info@isomat.eu**