

# TEAK OIL

## Wax oil for wood protection

### Description

Special mixture of oils and wax for protecting and refreshing the hard wood. Ideal for tropical timber of mahogany, iroko and teak, as well as all bare wood. It replaces the natural oils that are lost with time. It brings out the natural color of the wood and protects it against water and weather conditions, in general.

### Fields of application

TEAK OIL is used in any type of bare wood, garden furniture, wooden constructions, such as pergolas, etc. Suitable for both indoor and outdoor applications.

### Technical data

Form:	oil and wax solution
Color:	transparent
Density:	0.84 ± 0.02 kg/l
Viscosity:	25 mPa·s, at 23°C
Drying time:	3-4 h (touch dry)
Recoat time:	24-48 h

### Directions for use

The substrate must be clean and dry, unvarnished and free of dust, grease and resin. It is recommended to first treat the surface with sandpaper.

Slightly stir the content and then apply TEAK OIL undiluted onto the wood, using a cloth or brush. After approx. 5 min, the excess material that has not been absorbed must be removed with a dry cloth. In case of surfaces exposed to harsh weather conditions or in case of very absorbent surfaces, apply a second coat of TEAK OIL. In order to maintain or refresh the wood, apply TEAK OIL at least once a year.

Cleaning of tools:

Tools should be cleaned with SM-25 or WHITE SPIRIT while TEAK OIL is still fresh.

### Consumption

12-15m<sup>2</sup>/l, depending on the absorbency of the wood.

### Packaging

TEAK OIL is available in 750ml containers.

### Shelf life – Storage

24 months from production date if stored in original, unopened packaging at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

### Volatile Organic Compounds (VOCs)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory f (interior and exterior minimal build woodstains) is 700g/l (2010) for the ready-to-use product.

The ready-to-use product TEAK OIL contains a maximum of 680g/l VOC.

### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

#### MAIN OFFICES – FACTORY

17<sup>th</sup> km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

[www.isomat.eu](http://www.isomat.eu) e-mail: [info@isomat.eu](mailto:info@isomat.eu)